

VINYL INSTALLATION

Supplies

- Lettering
- Surface to apply it on
- Masking Tape
- Squeegee (Free for our customers)
- Surface cleaner (glass cleaner or rubbing alcohol)
- Tape measure or ruler
- Pin or needle

Step 1. Clean the surface where the lettering is to be applied thoroughly with glass cleaner or rubbing alcohol to remove all oil and dirt. (Apply decals on a warm surface between 50°F and 80°F)

Step 2. Position lettering on surface with masking tape and measure.
(Then measure again!)



Step 3. Apply masking tape horizontally over the top edge of the lettering to serve as a hinge.



Step 4. Cut between each letter or number so that each is independently hinged from the top. (Skip this step and go to step 5 with small lettering or one piece decals)



Step 5. Raise the lettering up over the top hinge and peel the liner back a few inches at a time.



VINYL INSTALLATION

Step 6. Hold lettering away from surface with one hand & allow adhesive to touch only as pressure is applied with a squeegee. Start at the top center of the lettering working down and outward to each edge of mask. Then go back to the top and work down again.



Step 7. Peel back the application tape slowly, making sure all of the lettering or decal is stuck to the surface.



Step 8. Inspect the decal for air bubbles or wrinkles. Poke any trapped air with a pin and press with fingers. Stand back and your installation is complete.

